



INTRODUCTION

The P7030EPVA Argus®4 External Power and Video Adaptor allows an Argus®4 camera to be powered from an outside source and for the video to be viewed over a wired network connection.

When used with a suitable camera variant this unit also allows analogue video to be viewed on a monitor via the BNC connector. This requires a camera with the additional analogue output function, P7130/A, P7225 or P7250.

The P7030EPVA can be powered from a wide DC input source and is supplied with a vehicle accessory plug.

The P7030EPVA replaces the Argus®4 integral battery pack on the top of the camera. Operating the camera on/off button is no longer required as the camera will turn on automatically when power is applied to the EPVA.

The camera will display a start-up screen until a usable thermal image is produced. The video output is enabled either by using the transmit button function on the camera or by using the customer software.

The P7030EPVA is constructed from durable materials with high resistance to heat, water and impact. No end-user maintenance is required other than external cleaning with a soft cloth.

FEATURES

- 10 V – 32 V input voltage.
- Automatic camera switch-on.
- Standard or industrial Ethernet connectivity.
- Standard NTSC video output on suitable camera types
- Crossover wired for simple direct connection to computer.
- Remote viewing potential over network.
- Vehicle accessory plug power input.
- Compatible with both router and direct connection.

APPLICATIONS

- Argus®4 camera in a fixed location, such as a training centre.
- Locating a camera on aerial platforms.
- Demonstration and training.

WARRANTY AND SUPPORT

The P7030EPVA is supplied with a 12-month warranty as standard.

Note: The P7030EPVA is not certified for automotive use in immunity-related functions. It may not be used for the control of a vehicle, a vehicular safety system or in a way that may disturb the driver, data bus or statutory devices fitted to a vehicle.

Whilst e2v technologies has taken care to ensure the accuracy of the information contained herein it accepts no responsibility for the consequences of any use thereof and also reserves the right to change the specification of goods without notice. e2v technologies accepts no liability beyond the set out in its standard conditions of sale in respect of infringement of third party patents arising from the use of tubes or other devices in accordance with information contained herein.

e2v technologies (uk) limited, Waterhouse Lane, Chelmsford, Essex CM1 2QU United Kingdom Telephone: +44 (0)1245 493493 Facsimile: +44 (0)1245 492492

e-mail: enquiries@e2v.com Internet: www.e2v.com Holding Company: e2v technologies plc

e2v technologies inc. 520 White Plains Road, Suite 450, Tarrytown, NY10591 USA Telephone: (914) 592-6050 Facsimile: (914) 592-5148 e-mail: enquiries@e2vtechnologies.us

TECHNICAL SPECIFICATIONS

Electrical and Interface

Power	Connector	Vehicle accessory plug, centre positive, 2 A fuse
	Input voltage	10 – 32 V (12 V and 24 V vehicle systems)
	Power consumption	Typically 5 W with camera operating
Data	Connector	Woodhead RJ-Lnxx series. Compatible with standard RJ45
	Format	320 x 240 pixel colour camera image at 10 fps MPEG 4 RTSP video stream over port 554 at 600 kb/s. Wired as a crossover configuration
Video	Connector	BNC 75 Ω
	Format	1 V p - p 75 Ω NTSC 525-line 60 Hz (EIA RS-170)

Mechanical

Battery replacement unit (H x W x D)	60 x 125 x 65 mm (2.4 x 5 x 2.5 inch)
Interconnect cable	1.7 m (67 inches)
Junction box (H x W x D)	60 x 120 x 80 mm (2.4 x 4.7 x 3.2 inch)
DC cable	1.2 m (48 inches)
Weight	690 g (1 pound 8 oz.)

Materials

Battery replacement unit	Radel [®] R-5100 and Lexan 940
Cable	Premium PVC flame resistant to UL-VW-1
Junction box	Flame retardant ABS UL V-0
DC cable	Premium PVC flame resistant to UL-VW-1

Compliance

RFI/EMC Emissions:	
LAN Mode	2005/83 EC EN55022 : 2006 Class A FCC CFR-47 Part 15 Class A ICES-003 Issue 4 AUS/NZ CISPR22 : 2006
Video Mode	BS EN 61000-6-3:2007 FCC Part 15B class B ICES-003 Issue 4 AUS/NZ 61000-6-3:2007
RFI/EMC Immunity:	
LAN Mode	2005/83 EC EN55024A2 : 2003
Video Mode	BS EN 61000-6-2:2005
Safety	IEC 60950-1 and related national standards
Vibration / Shock	BS EN 60721-3-2 Class 2M2
RoHS	All parts of the system are RoHS compliant as per EU directive 2002/95/EC

Environmental Data

Thermal conditions:	
Operating	Maximum operating temperature 75 °C (165 °F) Minimum operating temperature –10 °C (14 °F)
Storage	The EPVA can be stored for extended periods. It is recommended that for maximum effective operational life, the storage temperature be kept between –10 °C and +40 °C (14 °F and 104 °F) when not in use.

Environmental Protection

Battery replacement unit	IP56 BS EN 60529
Junction box	IP54 BS EN 60529